



MUFF COUPLING HOSE

Recommended Use:

Economical material handling suction or discharge hose designed for the transfer of bulk material, slurry, cement, gravel, grains, and abrasive products. Commonly used for gravity feed or low-pressure slurry applications in mines and quarries.

Features:

- Mandrel built with abrasion resistant rubber compound.
- Ideally used in areas where length is not defined.
- Designed to be used with Muff (split) Couplings TMCA or TMCC.
- Excellent UV resistance.
- Abrasion resistant wear tube.



Construction:

INNER TUBE: Black 6mm NR/SBR blend.
REINFORCING: high tensile textile cords with wire helix.
OUTER COVER: Black NR/SBR blend.

PRODUCT CODE	ID (mm)	OD (mm)	WORKING PRESSURE (psi)	BEND RADIUS (mm)	WEIGHT kg/m	COIL LENGTH (m)
TMCI-051	51	71	100	306	3.09	20
TMCI-076	76	103	100	456	4.93	20
TMCI-102	102	128	100	612	6.60	20
TMCI-127	127	157	100	762	8.80	20
TMCI-152	152	182	100	912	12.10	20
TMCI-203	203	234	100	1218	17.30	10
TMCI-254	254	287	100	2032	22.10	10
TMCI-305	305	344	100	2440	31.20	10

