



MARINE EXHAUST HOSE

Recommended Use:

Corrugated marine hose used for wet exhaust and cooling heat exchangers on boats. A lightweight corrugated hose designed for extra flexibility and can be used in various light duty applications. Other sizes & larger diameters available by request and can be made with thicker wall for heavier duty applications.

Features:

- Mandrel built wrapped rubber hose.
- Excellent sea water resistance.
- Working temperature range of -30°C to +100°C.
- Lloyd's Approved + SAE J 2006:13 R2- ISO 13363: 2016 Type 2 Class B.
- Cover resistant to abrasion, heat, and marine environment.



Construction:

- INNER TUBE:** Black NBR/SBR blend.
- REINFORCEMENT:** High tensile textile cords & helix wire embedded.
- COVER:** Black corrugated NBR/SBR blend.

PRODUCT CODE	ID (in)	ID (mm)	OD (mm)	WORKING PRESSURE (psi)	Weight kg/m	COIL LENGTH (m)
TME-025	1"	25	36	45	0.60	20
TME-032	1.1/4"	32	42	45	0.65	20
TME-038	1.1/2"	38	48	45	0.76	20
TME-045	1.3/4"	45	56	45	0.89	20
TME-051	2"	51	60.5	45	1.00	20
TME-057	2.1/4"	57	68.5	45	1.23	20
TME-060	2.3/8"	60	71	45	1.28	20
TME-063	2.1/2"	63	74	45	1.65	20
TME-076	3"	76	85	45	1.97	20
TME-089	3.1/2"	89	99	45	2.50	20
TME-102	4"	102	111	45	2.79	20
TME-115	4.1/2"	115	126	45	3.12	20
TME-127	5"	127	139	45	3.40	20
TME-152	6"	152	166	45	4.70	20
TME-204	8"	204	222	45	10.9	10,15

