



FUEL-OIL SUCTION & DELIVERY HOSE

Recommended Use:

Light to heavy transfer suction & delivery hose for petroleum products and oil return lines. Designed to load and unload boats, rail, road tankers, wet exhaust & general industrial applications.

Features:

- Mandrel built wrapped nitrile rubber hose
- Excellent Oil, UV and abrasion resistance.
- Handles petroleum products up to 55% aromatic content.
- 10 Bar Working pressure with 3:1 safety factor.
- Working temperature range of -20°C to +80°C.



Construction:

INNER TUBE: Black NBR.
REINFORCEMENT: High tensile textile cords with steel wire helix.
COVER: Black NBR smooth cover with red stripe.

PRODUCT CODE	ID (mm)	OD (mm)	WORKING PRESSURE (psi) @ 20°C	WEIGHT Kg/m	BEND RADIUS (mm)	COIL LENGTH (m)
TPOS-020	20	29	150	0.60	125	20
TPOS-025	25	35	150	0.74	150	20
TPOS-032	32	42	150	0.90	200	20
TPOS-038	38	48	150	1.10	220	20
TPOS-045	45	55	150	1.61	230	20
TPOS-051	51	61	150	1.40	240	20
TPOS-063	63	75	150	2.10	355	20
TPOS-076	76	88	150	2.70	460	20
TPOS-102	102	116	150	3.80	610	20
TPOS-152	152	170	150	7.23	800	20
TPOS-204	204	225	150	13.50	1400	10

