



SUCKAFLEX HOSE

Recommended Use:

Heavy duty abrasion resistant suction hose for vacuum trucks or handling abrasives such as crushed rock, sand, pea gravel, cement powder, dry fertiliser, iron ore and grains where high flexibility is required.

Features:

- Light weight and flexible.
- Excellent abrasion resistance.
- Static dissipating with no ground wire.
- Working temperature range of -20°C to +60°C.
- Bi-directional.
- 3:1 safety factor.



Construction:

INNER TUBE: Black SBR rubber conductive.
REINFORCEMENT: Rigid PVC Helix, anti-shock.
COVER: Black SBR corrugated.

PRODUCT CODE	ID (mm)	OD (mm)	WORKING PRESSURE (psi)	WEIGHT Kg/m	BEND RADIUS (mm)	COIL LENGTH (m)
TSFA-038	38	47	45	0.55	80	30
TSFA-051	51	60	40	0.74	120	30
TSFA-063	63	75	35	1.31	189	30
TSFA-076	76	89	30	1.64	228	30
TSFA-102	102	118	30	2.63	306	30
TSFA-127	127	146	30	3.68	381	30
TSFA-152	152	171	30	4.58	608	30
TSFA-203	203	230	30	8.41	768	15.2

