



WATER DELIVERY HOSE 10bar

Recommended Use:

Robust water delivery hose for use in all sectors of industry including aquaculture, mining and hire companies where a product that exceeds lay flat durability is required.

Features:

- Higher durability than all PVC lay flat hoses.
- Large range of sizes.
- Custom sizes can be manufactured by request.
- Excellent Abrasion/UV Resistance to withstand Australian conditions.
- Good flexibility at low temperatures.
- Temperature range -25°C to 80°C.



Construction:

- INNER TUBE:** Black NR/SBR blend.
REINFORCING: High tensile textile cords.
OUTER COVER: Black NR/SBR blend with green stripe.

PRODUCT CODE	ID (mm)	OD (mm)	WORKING PRESSURE (psi) @ 20°C	WEIGHT kg/m	COIL LENGTH (m)
TWDI10-020	19	29	145	0.54	20
TWDI10-025	25	34	145	0.64	20
TWDI10-032	32	42	145	0.83	20
TWDI10-038	38	48	145	1.14	20
TWDI10-051	51	62	145	1.69	20
TWDI10-057	57	72	145	2.57	20
TWDI10-063	63	78	145	2.74	20
TWDI10-076	76	90	145	3.07	20
TWDI10-089	89	102	145	3.43	20
TWDI10-102	102	114	145	4.07	20
TWDI10-114	114	128	145	4.44	20
TWDI10-127	127	140	145	4.64	20
TWDI10-152	152	166	145	6.68	20
TWDI10-203	203	219	145	9.50	20
TWDI10-254	254	271	145	10.1	12
TWDI10-305	305	323	145	13.20	12

