



Hosetek PTY LTD 9 Ridgeway Road Edinburgh North, SA 5113 TEL: (08) 8252 6500 FAX: (08) 8252 6511

EM: <a href="mailto:sales@hosetek.com.au">sales@hosetek.com.au</a>
<a href="http://www.hosetek.com.au">http://www.hosetek.com.au</a>

## WHITE SANITATION SUCTION HOSE

## **Recommended Use:**

Designed specifically for the use in sanitation systems in boats, caravans, and recreational vehicles. 15% Nitrile blend gives this hose an excellent resistance to odour permeation.

## Features:

- Operating temperature -15°C to +60°C
- Flexible white hose with rigid helix.
- 15% Nitrile with excellent odour resistance.
- Designed for sewerage plumbing.
- Smooth inner tube to resist build-up of material.



## Construction:

**INNER CORE:** 

15% Nitrile Rubber blend with white PVC and smooth finish.

**REINFORCING:** 

Hard PVC helix.

**OUTER COVER:** 

White PVC.

| PRODUCT<br>CODE | ID<br>(mm) | OD<br>(mm) | WORKING PRESSURE (psi) | VACUUM<br>RATING<br>Hg (mm) | COIL<br>LENGTH<br>(m) |
|-----------------|------------|------------|------------------------|-----------------------------|-----------------------|
| TPPR-019        | 20         | 25         | 130 / 0.9              | 624                         | 20                    |
| TPPR-025        | 25         | 32         | 130 / 0.9              | 624                         | 20                    |
| TPPR-038        | 38         | 46         | 130 / 0.9              | 624                         | 20                    |

