



YELLOWLINE SUCTION HOSE

Recommended Use:

Heavy duty suction and discharge hose suited for extreme environments using high Nitrile to PVC ratio to make it very abrasion resistant. Especially suited to abrasive slurries, waste trucks, many chemical and high volume airseeder applications.

Features:

- Heavy duty suction hose that is very very flexible.
- Working Temperature between -10° C and 60° C
- Excellent abrasion resistance with sturdy external helix giving excellent flexibility and protection.
- Excellent UV properties with smooth bore to reduce friction losses.

Construction:

INNER TUBE: Black Nitrile/PVC blend with smooth finish.

REINFORCING: External PVC yellow helix.

OUTER COVER: Black Nitrile/PVC blend with external raised yellow helix.



| PRODUCT CODE | ID (mm) | OD (mm) | WORKING PRESSURE @ 20°C | BEND RADIUS (mm) | VACUUM RATING mm/Hg | ROLL LENGTHS (m) |
|--------------|---------|---------|-------------------------|------------------|---------------------|------------------|
| TYL-050 | 50 | 63.4 | 73psi / 0.5MPa | 350 | -800 | 20 |
| TYL-063 | 63 | 79.6 | 58psi / 0.4MPa | 380 | -800 | 20 |
| TYL-076 | 76 | 93.4 | 58psi / 0.4MPa | 400 | -800 | 20 |
| TYL-102 | 102 | 118 | 43psi / 0.3MPa | 600 | -800 | 20 |

