

BUTTERFLY VALVES – WAFER STYLE



PART NUMBER	IMPERIAL SIZE	H1	H2	H3	B
BFVE-050	2"	80	140	29	42
BFVE-065	2 1/2"	89	155	29	44.7
BFVE-075	3"	95	160	29	45.2
BFVE-100	4"	104	180	29	52
BFVE-125	5"	120	193	29	54.4
BFVE-150	6"	145	200	29	55.7
BFVE-200	8"	175	240	35.5	60.1
BFVE-250	10"	203	272	35.5	65.6
BFVE-300	12"	242	317	35.5	76.5
BFVE-350	14"	368	267	45	78
BFVE-400	16"	400	298	51.2	102
BFVE-450	18"	422	318	51.2	114
BFVE-500	20"	480	355	64.2	127
BFVE-600	24"	562	444	70.2	154

All valves available with gearboxes, pneumatic and electric actuators. Fail safe options. Please call for options.

Materials

Body	Cast Iron
Disc	50mm-300mm (SS316) 350mm - 600mm (NPD/CF8M)
Stem	SS416
Lever	Cast Iron
Seat	NBR or EDPM
Seat Options	Viton/ Teflon

Specifications

Max Working Temperature	80°C
Cold Working Pressure	1600kpa
Flange Drilling	PN10/PN16, ANSI 125/150, AS2129 D/E, JIS 10K/16K/20K

Applications

Plumbing, Mining, Irrigation, HVAC

