

BUTTERFLY VALVES – LUGGED STYLE



PART NUMBER	IMPERIAL SIZE	H1	H2	H3	B
BFVLE-050	2"	80	161	29	42
BFVLE-065	2 1/2"	89	175	29	44.7
BFVLE-075	3"	95	181	29	45.2
BFVLE-100	4"	104	200	29	52
BFVLE-125	5"	120	213	29	54.4
BFVLE-150	6"	145	226	29	55.7
BFVLE-200	8"	175	260	35.5	60.1
BFVLE-250	10"	203	292	35.5	65.6
BFVLE-300	12"	242	337	35.5	76.5
BFVLE-350	14"	368	267	45	78
BFVLE-400	16"	400	298	51.2	102
BFVLE-450	18"	422	318	51.2	114
BFVLE-500	20"	480	355	64.2	127
BFVLE-600	24"	562	444	70.2	154

All valves available with gearboxes, pneumatic and electric actuators. Fail safe options. Please call for options.

Materials

Body	Ductile Iron
Disc	50mm-300mm (SS316) 350mm - 600mm (CF8M)
Stem	SS416
Lever	Cast Iron
Seat	NBR or EDPM

Specifications

Max Working Temperature	80°C
Cold Working Pressure	1600kpa
Flange Drilling	AS2129 Table E

Applications

Plumbing, Mining, Irrigation, HVAC

